

City of Staunton, Virginia
Entrance Corridor Overlay District



Design Guidelines for Commerce Road

City of Staunton, Virginia
Entrance Corridor Overlay District



Design Guidelines for Commerce Road

Entrance Corridor Overlay District: Design Guidelines for Commerce Road

introduction: page 5

The Entrance Corridor Overlay District and the Comprehensive Plan
Map of the Entrance Corridor Overlay District
The Purpose of the Design Guidelines
Recommended Priorities for Development Review

recommendations for sites: page 12

General Site Design
Plants and Planting Patterns
Planting Configurations and Stormwater Management
Managing Site Plantings
Site and Building Signs
Site and Building Lighting

recommendations for buildings: page 20

Existing Resources
Re-developed Buildings; New Buildings

recommendations for community form: page 28

Design Guideline Areas along Commerce Road
Example Design Guideline Area sections
Rehabilitation Districts



Design Guidelines for Commerce Road
introduction

Introduction:

The Entrance Corridor Overlay District and the Comprehensive Plan

Throughout the years, many citizens have expressed the desire to protect the overall quality of life in the City of Staunton. The 2003–2010 Comprehensive Plan carries forward the following guidelines written to address the protection of quality of life in the City:

“...conserve and/or protect the City’s natural resources, historic character, and scenic qualities.”

“...encourage appropriate development and/or re-development of land within the City.”

The Priority Initiatives included in the Comprehensive Plan establish several specific goals to help accomplish these guidelines. Several of these Priority Initiatives directly address issues impacting the way we as a community should design and build within the Entrance Corridor Overlay District.

Regarding protecting the City’s natural resources and scenic qualities from the impacts of development and ensuring their conservation the Priority Initiatives include:

- Encourage developers to designate open space and environmentally sensitive areas first and then design developments around these elements.
- Reduce hard surface parking area requirements and increase landscaping and tree planting requirements for commercial development, re-development, and renovations.
- Discourage further development in the floodplains.
- Protect and enhance streams and creeks in and around the City, including Lewis Creek, Asylum Creek, Gum Springs Branch, and Poague Run. Activities may include: Undertake restoration where needed. Also encourage landowners to take advantage of cost-share programs for native trees and shrub plantings along stream and creek corridors running through private lands.
- In addition to these Priority Initiatives, steep slopes, karst geology are included as primary factors to consider in the context of new development. Establishing creative design standards are included as an approach to development without degrading Staunton’s scenic qualities.

Regarding protecting the City’s historic character from the impacts of development and ensuring its conservation the Priority Initiatives include:

- The City, working with neighborhoods and the Historic Staunton Foundation, should identify properties throughout the city of historic or architectural significance – especially those along entrance corridors, thoroughfares, and in transitional neighborhoods.
- Take steps to preserve the architectural character of older neighborhoods that may not be included under the “historic” category, but are equally important to the look and feel of the city, especially pre and post World War II neighborhoods.
- When developed, re-developed, or renovated require commercial and retail structures that adjoin residential areas to utilize architectural facades and site features that are consistent with and/or complementary to the surrounding neighborhoods.
- Develop alternative approaches to street designs in order to ensure that the roads and intersections are scaled to the neighborhoods.

Regarding encouraging appropriate development and/or re-development of properties within the City the Priority Initiatives include:

- Include “walkability” as a primary design criteria for all new public and private development and re-development projects.
- Encourage siting of parking lots to the sides or rear of buildings, where appropriate; move parking to the side and rear of commercial and public buildings, rather than the front.
- Provide incentives for retro-fitting excess hard surface commercial parking areas to landscaped areas.
- Require landscaping and safe, user-friendly pedestrian network with designated walkways and crossings within commercial and public parking areas.
- Scale commercial parking requirements to typical use rather than capacity use, by lowering the minimum level of parking required and limiting the total amount of hard surface parking permitted.
- Require appropriately landscaped and sized sidewalks in all new developments or major re-developments with established design, maintenance standards for sidewalks based on area density and proximity to primary pedestrian destinations.
- Examine lot size, setback, and parking requirements for opportunities to improve flexibility in older neighborhoods and re-development areas.
- Seek ways to control light pollution. Examples include: require appropriate light fixtures for all new commercial and public facility development, re-development, and renovations.
- Reduce parking requirements by allowing and promoting shared parking and dual use especially for re-development, transitional areas, and planned mixed-use development.
- Educate the public, development community, local officials and staff on the principles and advantage of smart/good development (environmental, health, and financial).
- Support enhancement and priority implementation of the City’s Master Landscaping Plan especially along entrance corridors and the pedestrian network.


The guidelines and priorities outlined in the Comprehensive Plan reconfirm the desire among the citizens of Staunton to conserve and protect the City’s natural resources, historic character, and scenic qualities and encourage pedestrian friendly, human scaled development. Since 1747, the people of Staunton have built and lived in response to surrounding natural conditions leaving a legacy of streets, alleys, buildings, parks, gardens, and farms, by and large resulting in human scaled environments rich in multiple types of managed landscapes and styles of architecture. Learning from and applying historic approaches to building in Staunton while respecting the City’s natural context and heritage have been central concepts in the development of these design guidelines.



Built within the ridge and valley topography typical of the Shenandoah Valley, the City of Staunton evolved in response to a dynamic and complex landscape. Historic downtown is located between two treed ridge lines with adjacent residential districts eased onto the near-by hills. These hills and masses of mature trees provide the green back drop for the City. Historical approaches to building uses structures to negotiate topographic changes, including terracing and site walls; disruption in the topography is in scale with the human body and once work was completed, has allowed the overall character of the slope to remain intact.

Map of the Entrance Corridor Overlay District

Adopted April 10, 2008



The Purpose of the Design Guidelines

The Entrance Corridor Overlay District Ordinance and the Design Guidelines:

The Entrance Corridor Overlay District is intended to implement the City of Staunton's Comprehensive Plan goal of protecting the city's natural, scenic, historic, architectural and cultural resources. The passing of the ordinance on April 10, 2008 meets this Comprehensive Plan goal by establishing design standards within the ordinance and providing design guidelines for each corridor, ensuring the compatibility of development, redevelopment, and adaptive reuse proposals with the resources identified in the comprehensive plan as important. The ordinance and design guidelines promote the general welfare of the community by creating attractive human-scaled environments; increase commerce; improve property values; and increase public awareness of the natural, scenic, historic, architectural, and cultural resources near and outside the City's historic preservation districts.

The Entrance Corridor Overlay District ordinance provides standards for design expectations all of the corridors share such as the height of signs, the width of beds for plants, and the placement of utilities underground. But since each of the corridors has unique characteristics, these design guidelines provide recommendations for approaches to site and building design that perpetuate these unique characteristics. Our first step was to look carefully at Commerce Road based on the expectations of the Comprehensive Plan for the Entrance Corridor Overlay District. Each of the designated entrance corridors has unique strengths, challenges, and existing resources. In order to begin to understand the dynamics along each road City staff conducted general site analysis, researching and mapping traffic levels, setbacks and square footage of commercial buildings, patterns of commercial history, and natural resources along Commerce Road. These design guidelines are based on identifying and amplifying these existing strengths, with the understanding the Comprehensive Plan has focused our priorities on development perpetuating, rather than erasing, the existing character of Commerce Road.

Commerce Road:

Commerce Road begins at its intersection with Greenville Avenue near the underpass, continues along the banks of Lewis Creek towards the north / northeast until reaching the City limits north of the Woodrow Wilson Parkway. Zoning districts along the length of Commerce Road includes B2, B3, P1, R1, R2, R3, I1, and I2. Large areas of agricultural land and working farms lie adjacent to Commerce Road including near-by land included in one of the City's Agricultural and Forestal Districts. The mixed use history of these corridors is long and well established; annexations dates along Commerce include 1860, 1905, 1948, and 1956. Before building booms, post 1950s, the dominant land use adjacent to Commerce Road (Route 11) was agriculture, with industrial, institutional, and local business uses within the 1860 and 1905 areas of annexation. Given the topographic conditions along most of Commerce Road, coupled with the presence of floodway and flood plain areas of Lewis Creek and tributaries, these recommendations for the scale and character of future development rely heavily on existing examples of building scale, current building code considerations, and retaining the presence of the agricultural and forestal landscape. Recommendations include maintaining and / or establishing forested edges and hedgerows along sections of Commerce Road, establishing the character of a rural parkway, creating a buffer for possible development, and allowing for a matrix for building pedestrian and bike trail network throughout the City in the future.

Traffic counts vary greatly along the length of Commerce Road. From Coalter Street to Statler Boulevard, the Virginia Department of Transportation figures for 2006 place the Annual Average Daily Traffic between 1,000—4,999 trips. From Statler Boulevard to Augusta Street, 5,000—9,999 trips; from Augusta Street to Woodrow Wilson Parkway, 10,000—14,999 trips, and from the Woodrow Wilson Parkway to the Staunton city limits, 15,000—19,999 trips.

Recommended Priorities for Development Review

Exempt from all Entrance Corridor Overlay District review:

- All legally non-conforming buildings, sites, signs, walls, plants, walkways, entrances, parking lots, etc.
- Single family residential buildings and sites
- City, State, and Federal Government facilities

Applicability of the Design Guidelines:

- When the areas of any parcel beyond 1,200 feet from an adjacent corridor are not visible from an adjacent corridor, it is recommended that the areas not visible from an adjacent corridor be exempt from the Design Guidelines. (*as amended, 2.10.11*)

Full Entrance Corridor Overlay District review to include placing overhead utilities underground with parcel boundaries; planting requirements; providing pedestrian and vehicular access; building placement, architectural character, etc.:

- New or major re-configuration of a site development plan.
- Construction of a new building
- Major re-construction or alteration of the size, shape, or facade of any building, including relocation of any doors or windows or removal or alteration of any architectural features, details, or elements.
- Major reconfiguration of the corridor such as the addition or removal of medians, the addition of turning lanes, addition of curb and gutter or sidewalks, etc.
- Any site development involving the relocation or removal of overhead utilities.

Partial Entrance Corridor Overlay District review to include planting requirements, providing pedestrian and vehicular access, architectural character, etc.:

- Additions to existing site development plans resulting in changes of less than 50% of the existing site configuration.
- Construction of and addition to an existing building resulting in an increase of less than 50% of the total square footage of the existing building.
- Expansion of parking lots resulting in an increase of less than 50% of the total square footage of the existing parking area.
- Minor changes in the corridor to include lane striping and similar activity
- Additions to existing planting resulting in an increase in 50% or more of the existing site plantings.

Review for Entrance Corridor Overlay District signs:

- Re-facing of existing site signs; continuing businesses
- Re-placement of all signs and sign supports: all changes of business or change in use on existing site
- Addition of all new site signs

Review for Entrance Corridor Overlay District lighting:

- Addition of all new exterior lighting

Right-of-Way responsibilities:

- It is recommended the owner or occupant of any land or premises abutting upon any public street right-of-way, including the sidewalk and between the sidewalk and the curb, maintain all plantings whether installed by the property owner or occupant or City of Staunton.




***Design Guidelines for Commerce Road
recommendations for sites***


Recommendations for Sites:

General Site Design

- Establish priorities for site design based on integrating existing land forms, stream beds, or significant plant communities into the development of a site. By emphasizing site design that integrates these characteristic resources rather than eliminating them, the essential natural and scenic qualities unique to Staunton remain consistent regardless of the changing needs of business development. Slopes of 25 percent or greater should remain undisturbed and used to provide recreation and watershed protection.
- Avoid overly tall retaining walls, earth plinths, or excessive cut and fill. Over scaled walls and earth plinths disrupt or eliminate characteristic land forms, eliminate existing trees and other plants, isolate development from adjacent sites and create environments out of scale with human physical dimensions. Site retaining walls should be in proportion with the building and relate to building elements such as water tables and foundations.
- Utilizing incremental land terraces is recommended; using buildings to negotiate changes in elevation, constructing retaining walls in scale with human proportions, and blending grading smoothly into the surrounding topography are approaches historically employed in the Shenandoah Valley landscape. Where existing land forms have been previously disrupted, approaches to grading should attempt to re-establish the overall character of the pre-existing land forms.
- Sites should not be used as long term borrow pits or for fill storage.



Schematic terracing of parking lots and buildings




Schematic terracing of parking lots and buildings; detail

- Resulting soil quality and structure on heavily disturbed sites should be carefully considered in terms of their practical ability to support long term plant growth. Appropriate species choice and site reclama-

tion may be useful components of site design considerations.

- Site rehabilitation efforts involving the reclamation of large areas of impervious surface should utilize the Center for Watershed Protection publication Urban Stormwater Retrofit Practices Version 1.0 published in August, 2007 for appropriate guidelines and recommendations.
- Options for the location of parking include side and back of buildings with limited consideration for parking between the corridor and building, as well as locating parking in front of buildings. Provide terraced parking lots to integrate existing land forms. It is recommended consideration be given, in the context of required off street parking, for establishing a single row of parking spaces adjacent to the corridor for the display of vehicles, boats, and similar items.
- Retaining walls resulting from site terracing should be in scale with the building foundation and human dimensions. Provide site walls to reflect established material traditions: local stone, concrete, or brick are appropriate materials for walls along West Beverley Street. Fencing may include wood and metal. Chain link fencing is not recommended.
- Site design should include sidewalks providing planted, pedestrian passage: connecting parking lots to buildings within the site; connecting to adjacent parcels; connecting to adjacent neighboring communities; with the overall intent of allowing for comfortable and useable pedestrian access throughout the corridor.
- Site design should allow for vehicular connections between adjacent sites.



options for parking configuration

Plants and Parking Areas

The following plantings are recommended for parking areas:


- One large canopy tree inside the parking lot for every ten spaces provided; planted at 2" caliper, dbh, minimum; 15' tall for multi-stemmed trees
- One large canopy tree at the rate of 25' on center along the full perimeter of the parking lot, planted at 2" caliper, dbh, minimum; 15' tall for multi-stemmed trees
- An evergreen hedge, 3½' tall, whenever parking is located adjacent to a sidewalk on the corridor; plants to be a minimum of 18" tall (measured from the top of the soil) upon planting. Evergreen hedges shall be maintained at no wider than 3½'; it is recommended no hedge, or other site feature, be permitted which materially impedes vision at vehicular entrances or exits to and from a property. Limiting species

choices for hedges to species demonstrating mature height and width characteristics appropriate for the use is recommended.

- Large canopy trees along vehicular passageways at the rate of 25' on center
- Sub canopy trees along all pedestrian passages at the rate of 15' on center, planted at 2" caliper, dbh, minimum; 15' tall for multi-stemmed trees.
- All plantings shall be subject to American Standard for Nursery Stock/ ANSI Z60 2004-1 for minimum root ball size, transplanting standards etc.



Hedge planted between sidewalk and adjacent parking lot; this planting includes trees



An example of a pedestrian walkway through the center of a parking lot with integral bioretention in the parking lot islands.

Plants and Planting Patterns

Natural, horticultural, and agricultural traditions along Commerce Road include the following planted types that may be utilized in site design :

- Existing Forest and Woodland: Forest and Woodlands are complex systems of plants, surface litter, and soil, functioning in the larger landscape as sponges; absorbing and filtering rainwater as it falls. Because

of this function, mature forests and woodland dominated by indigenous species are best preserved when ever possible, integrated into the overall design of the site and managed in conjunction with state and county urban forestry consultation. Site design focused on preserving trees through thoughtful grading practices and strategic integration of existing forests and woodland have the advantage of the immediate presence of mature plantings on site. Large stands of trees contribute to reduced site runoff; reducing the need for costly storm water infrastructure and helping to control erosion.

- **Re-forestation:** Re-forestation is a viable option for developed landscapes. Land too steep for buildings and sites typically kept with large areas of mown lawn are areas that may benefit from reforestation efforts. Using near-by indigenous forest and woodland as a guide is an effective approach to begin re-establishing forest and woodland species combinations lost in the process of land development. Forest and woodland plant communities vary with moisture conditions, soil type, and elevation; re-plant what was there as closely as can be ascertained. For assistance and more information about the management of forest and woodland fragments contact the Virginia Department of Forestry at <http://www.dof.virginia.gov/index.shtml>
- **Riparian Plant Communities:** Lewis Creek's influence on the Commerce Road corridor impacts the entire length of the corridor, not only in terms of the presence of the creek itself, but the presence of the floodway on adjacent properties. Creeks, like forests and woodlands are complex systems of water, plants, and geology, functioning as a transition area between higher elevations in the watershed and the Chesapeake Bay. Plant communities, as part of the overall creek system, serve to slow the velocity of stormwater run off, prevent erosion, and filter non-point pollution. Site design focused on preserving and managing indigenous riparian plant communities through thoughtful site design and maintenance is encouraged; the re-establishment of riparian plant communities as part of site design is encouraged as well. The publication *Riparian Buffers Modification and Mitigation Guidance Manual* by Baird and Wetmore, published by the Chesapeake Bay Local Assistance Department is recommended as a resource for managing riparian plant communities.
- **Topography and Indigenous Plant Species:** In addition to forests and woodlands, existing conditions both on site and near-by can provide a wealth of clues regarding which species of plants naturally grow well in various conditions. Many of these plants can be utilized in developed landscapes, their use contributing to more easily sustained plantings when properly sited. Potential long terms savings could be seen in reduced need for water and fertilizer, which benefits both the property owner and the health of the watershed. In addition, planting indigenous plants in developed landscapes creates a sense of consistency in the overall landscape, helping to strengthen a sense of place.
- **Hedgerow:** Planted for centuries to divide agricultural areas, create microclimates for cultivating crops, buffer buildings from harsh weather patterns, and to serve as fences, hedgerows have a strong presence in the historic landscape of Staunton. Because they are used in multiple ways, hedgerows are simultaneously a natural, cultural, and historical landscape resource. Hedgerows are comprised of combinations of multiple tree and shrub species arranged in a wide band and may be larger or smaller in scale depending on the species included in the planting. Developed areas could benefit from hedgerow plantings particularly in areas able to take full advantage of the density and sense of enclosure inherent in this type of planting. Historically typical Virginia hedgerow species include *Maclura pomifera* (Osage orange), *Crataegus* species (Hawthorns), *Ilex* species (Hollies), *Viburnum* species and *Juniperus virginiana* (Eastern Red cedar); in the developed landscape, hedgerows could be created with a wide range of plant species combinations. Hedgerow type plantings lend themselves very well to storm water management systems integrated into site design such as bioretention.
- **Orchard:** Staunton has a long history of fruit production within the city limits as well as in near-by Augusta County. 1950's aerials of the Commerce Road vicinity include extensive orchard production. Fruit tree species common to orchard production in Virginia are apples (*Malus* sp.), peaches (*Prunus persica*) and pears (*Pyrus communis*). Orchards are typically planted in multiple, parallel rows forming a grid pattern. This pattern of planting facilitates pruning, fruit harvest and the movement of air through

the trees. Virtually all tree species can be planted in a grid pattern which is easily integrated into site design comprised of the right angles typical of many developed sites.

- **Hedges:** Hedges are rows of closely spaced trees or shrubs planted to form a barrier between two distinct areas of a site. Hedges can establish boundaries, buffer a view, direct movement, or frame a view. A hedge along a roadway can be used to minimize the noise and movement and create distance and a sense of safety between pedestrians and near-by traffic. Hedging plants range from the smallest of shrub species to closely spaced trees and may be formal or informal in character. Hedging plants may be clipped into geometric forms, pruned to establish a more textured, irregular form, or allowed to grow into a more informal outline. Choosing a species that will mature at the height desired is the easiest way to establish an informal, low maintenance hedge.

Planting Configurations and Stormwater Management

The design of stormwater management systems such as bioretention are based on the natural ability of forests and woodlands to absorb and filter large amounts of rainfall. This process of absorption and filtering reduces the amount, velocity, temperature, and quality of rain water as it impacts local watersheds. When we clear and for development and replace indigenous plant communities, this mechanism for absorption and filtering is lost. By integrating plantings and soil profiles mimicking this natural system (like bioretention) in smaller increments throughout developed areas, such as parking lots, this function can be reestablished to a large degree. Including these kind of plantings throughout developed areas significantly impacts the quantity, velocity, temperature, and quality of stormwater runoff from paving and buildings.

- It is recommended provisions for stormwater management be surface based, integrated into developed areas incrementally, and utilize plant based systems of treatment.
- Stormwater ponds are discouraged.

Managing Site Plantings

- **Management of Invasive Species:** Plants included on the Virginia State or Federal lists of invasive exotic plants species should not be planted in the Entrance Corridor Overlay District and should be selectively or wholly removed from all sites as part of a larger landscape management strategy. In particular, remnant forest, woodland, and hedgerows require managing the presence of invasive plant species.
- **Pruning and the Maintenance of Trees and Shrubs:** Please refer to ANSI A 300 Part 1- Standards for pruning.
- **Right-of-way responsibilities:** It is recommended the owner or occupant of any land or premises abutting upon any public street right-of-way, including to the sidewalk and between the sidewalk and the curb, maintain all plantings whether installed by the property owner, occupant, or the City of Staunton.

Site and Building Signs

Sign characteristics not recommended include:

- **Floating sign.** A sign that is a moored balloon or other type of tethered floating sign.
- **Lighting of any type** outlining any structure or window
- **Pennants, ribbons, spinners, streamers.** Pennants, ribbons, spinners, streamers or similar moving devices, whether or not they are part of a sign
- **Sign that contains or consists of searchlight, beacon or strobe light.** A sign, other than a public sign, that contains or consists of a searchlight, beacon, strobe light, or similar form of illumination
- **Sign that produces sound.** A sign that produces sound for the purpose of attracting attention regardless of whether the sign has a written message content
- **Sign with unsafe illumination.** A sign that is illuminated so as to be unsafe to vehicular or pedestrian traffic

- A commercial window sign affixed to a window or door above the first floor of the structure unless the business to which the sign pertains does not occupy any first floor space
- Advertising vehicles, where the vehicle is parked so as to be visible from a public right-of-way in a parking space or parking area not associated with a car dealership; the vehicle is inoperable; or the vehicle is incapable of moving on its own or is not self-propelled.
- Banners, except as a temporary sign
- Billboards
- All roof signs
- LED display signs are not on the list of permitted signs in the Entrance Corridor Overlay District, the ordinance does allow staff to consider additional types of signs for approval. LED displays are very energy efficient which is good for both the property owner and the community. However LED signs can create glare, spillover light onto adjacent properties, and if they blink on and off create a distraction for drivers. With these considerations, the use of LED displays along Commerce Road may be supported with the following conditions: The LED display should consist of red diodes on a black background. The LED display be turned off after the business closes; The LED display shall not move or change within a 24 hour period; Should an LED display cause undue glare on adjacent properties or from nearby Commerce Road, the light levels should be dimmed and maintained at the reduced level.
- Sign bases should reflect site material and construction traditions. Stone and brick are appropriate materials; metal bases will be considered on a case by case basis.
- To provide consistency throughout the Entrance Corridor Overlay District, all channel letters and bubble signs should have dark bronze trim caps and returns; raceways should be painted to match mounting surface.
- Neon signs will be considered if used as part of a freestanding sign or sign located on a building face; neon tubing used to outline, edge, or otherwise emphasize building or site features is discouraged.
- Text and logos only on gas station canopies may be internally illuminated; the overall internal illumination of gas station canopies is discouraged.
- Small, standardized, neon “OPEN” signs are recommended; all other lighted signs located in building windows is not recommended.

Site and Building Lighting

Because Commerce Road is a mixed use community the use of full cut off site, building, and canopy lighting fixtures only is recommended on fixtures emitting over 1800 lumens. To provide consistency throughout the Entrance Corridor Overlay District, all site and building light fixtures should be dark bronze in color.

General Site Design Exceptions

Retention of intact building and site combinations more than 50 years old from the date of adoption of these guidelines may be considered based on the design history and typical patterns of use.



***Design Guidelines for Commerce Road
recommendations for buildings***

Recommendations for Buildings:

Existing Buildings as Design Sources

The Comprehensive Plan includes the protection of historic structures in changing areas as a policy goal. Staunton's unique cultural and historic characteristics are expressed in its remaining commercial buildings, industrial buildings, residences, cemeteries, site elements, and site configurations. While the Entrance Corridor Overlay District does not require the preservation of these buildings, we hope to encourage their retention and creative re-use, as well as offer them as examples for helping determine the character of future development and re-development projects on Commerce Road.

Buildings remaining from early points in the history of the street contribute to the character, mark the growth and location of the local community, and refer to cultural content in a manner that cannot be replaced or duplicated. Because of their value to the community, the adaptive re-use of existing historic buildings and site structures is encouraged in the Entrance Corridor Overlay District. Federal assistance through the National Park Service for the rehabilitation of historic buildings not located in historic districts may be available for property owners; contact <http://www.nps.gov/history/hps/tps/tax/brochure1.htm#10> for additional information. Staunton City and Virginia State incentives may be available for the rehabilitation of existing buildings for use as businesses in portions of the Entrance Corridor District overlapping the City's Enterprise Zones; please refer to the Staunton City web site for further information. <http://www.staunton.va.us>

The intent of this section of the design guidelines is to improve the quality of new and re-developed buildings. The Entrance Corridor Overlay District ordinance requires the design of adaptive re-use and newly constructed buildings based the scale, massing, materials, and construction methodology and manner of negotiating changes in elevation of near-by historic resources. Included below are examples of existing buildings with characteristics that may be used to inform new building design. Please note the replication of historic buildings is not encouraged; mimicking historic architecture may contribute to a misleading sense of historic development.





Ingleside Resort Country Club; appears in 1954 aerials; likely operated as a resort continuously since opening in 1928: Ingleside Resort Country Club is an existing suite of approximately 11 buildings, constructed, in part, to serve the adjacent golf course to the west. Included on site is an existing neon “Ingleside” sign mounted on three steel pilings. The sign and mounting structure are approximately 50’ wide by 75’ tall and are likely original to the resort development. Total square footage of the hotel is approximately 45,000. The suite of resort buildings are aligned with an existing ridge line and are terraced into the land form. The hotel building includes a closed pediment roof on a central section of first and second story porches that extends outward from the face of the building. The porches span the full front of the building and include Chippendale railings. The main body of the building is red brick. The banquet building, located to the southwest of the hotel is a masonry / stucco building, flat roof with a parapet and crown molding, arched windows with fan lights and 15 over 15 sash windows with square pilasters between each window, and exposed red brick foundation. The front of the building features a closed pediment roof at the main entrance to the building. Included on site is an existing neon “Ingleside” sign mounted on three steel pilings, approximately 50’ wide by 75’ tall, is likely original to the resort development, and is a strong example of neon signs of the period.



Vernacular agricultural buildings: Agricultural buildings are built to house animals, store hay and supplies, or provide space for machine repairs and other everyday maintenance activities. Their presence in the agricultural landscape of historic and contemporary Commerce Road is a constant. Typically frame structures constructed on stone, brick, or other masonry foundations, with roofs most often comprised of gable and cross gable forms with cupolas. Farm buildings are often very large, open, simple structures; lending themselves to multiple uses. Because of their size and simple forms, they are a useful design source for new buildings serving many purposes. The footprint of the older barn illustrated is approximately 4,800 square feet.



One small gas station, post 1954 and a fuel distribution facility that appears in the 1954 aerial; both located in Augusta County until annexed in 1987: While very different in architectural style, these facilities are similar in scale and typical of buildings located along the section of Commerce Road wedged between Commerce Road to the west and the railroad tracks to the east. Both buildings are painted masonry, feature large, multi and single paned windows on all façades. The post 1950's roof is shed in overall form, with a triangular extension forming the building's porte cochere. The pre-1954 building features a gable roof with dormers with a flat roof over the garage area and porte cochere. While the area between the repair shops and the corridor were likely used for parking, there are also parking areas included to the side of the buildings. The total square footage of both of these buildings is under 2,000.


General Building Characteristics

Based on the strengths of the example buildings provided as a source for design characteristics, the following recommendations are provided:

- New buildings should include one or a combination of the following materials/methods of construction: wood frame, fiber cement, and stucco siding; brick, stone, or concrete foundations; brick construction or brick facing; stone site wall/foundation combinations; finished concrete block; roofing material may include standing seam metal, asphalt shingle, and rubber membrane/parapet on flat roofs.
- Site walls retaining walls should be comprised of: stone, brick, or concrete; stone or brick facing on a concrete or cmu wall. The use of segmental/modular concrete block is discouraged. Site walls should be considered as part of site terracing in increments; site walls out of proportion with building foundations or the human figure are discouraged.
- The building foundations themselves or integral site walls are used to take up changes in elevation from the front of the building to the back. The first floor of the building is either located partially below grade at the back of this building with the brick foundation is stepped towards the rear or vice versa. The buildings utilize combinations of terracing into and building above the surface of the existing land form. Auxiliary spaces in buildings created by elevation changes create possibilities for additional useable space or provide areas to conceal the buildings mechanical systems.




topographic contours indicate a continuation of the land form from one side of the building to another; with very large buildings, placing part of the building underground can help reduce negative impacts of a building out of scale with its surroundings



topographic contours indicate the earth has been pushed aside to create a flat spot for the building, eliminating characteristic land forms

- Roof forms recommended include gable, cross gable, open and closed pediments, and flat forms.
- Site materials recommended include local stone, asphalt, concrete, and exposed aggregate concrete.
- The building examples provided include transitional areas from the outside to the inside of buildings. These areas provide protection from the elements, allow areas for outdoor dining and gathering, provide covered walkways connecting business to business, and help modulate the scale of multi-storied buildings. It is recommended the front of all buildings include a transitional area a minimum of 15 feet deep; this area may be an attached porch, breezeway, colonnade, or other similar element; a minimum of one third (5 feet) of this area must be fully protected from the weather. Transitional areas may extend fully outside of the main building face, extend fully inside the main building face, or combine interior and exterior elements.




schematic strategies for combining types of transitional areas



examples of porches and breezeways in new buildings

These examples also include variations in the overall form of the buildings. The surfaces of simple box forms have been activated with variations in the surface of the building, with of the buildings including a variety of windows on all elevations; tinted glass is discouraged. New building elevations should include a minimum of three surface variations a minimum of 8 inches deep; variations a minimum of 2 feet deep should be provided when tied to a change in the roof line.




schematic variations in building form

- Windows are recommended to provide interest and surface variations on building elevations. Building walls without windows are discouraged.




variations in overall building form on new buildings


- The design of gas station canopies, building canopies and other accessory structures should be compatible with the scale, color, materials, and detail of the buildings they serve.
- For the purposes of the design guidelines, the following definitions of exterior building walls and roofs shall apply. The definition of building walls and roofs is important when the use of walls and roofs for the display of signs for example: signs attached to walls are recommended in the Entrance Corridor Overlay District; the use of any signs attached to building roofs is not recommended. (*as amended, 2.10.11*)




flat; walls




flat; roof




parapet; walls




parapet; roof




shed; walls




shed; roof




gable; walls




gable; roof




hip; walls




hip; roof




mansard; walls




mansard; roof



gambrel; walls




gambrel; roof



***Design Guidelines for Commerce Road
recommendations for community form***

Design Guideline Areas along Commerce Road



Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nts

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			



Entrance Corridor Overlay District: Commerce Road
proposed design guidelines areas



DNB

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A

section/plan B


section/plan C



floodway

stream buffer





Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nts
note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			




Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nts

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			




Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nfs

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			



Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nts

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			




Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nts

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			



Entrance Corridor Overlay District: Commerce Road
proposed design guideline areas



nts

note: map elements depicted are representations and are not to be construed or used as legal description; this map is for display purposes only

section/plan A		floodway	
section/plan B		stream buffer	
section/plan C			


Section/Plan A

Section/Plan A

- These areas of these corridors include the smallest parcels with buildings closest to the street and existing sidewalks; these areas include frequent adaptive reuse of existing buildings; a large presence of residential uses currently exists
- Existing sidewalks should be retained or replaced where missing or badly damaged
- Recommended range of total square footage for new buildings: from 2,000 to 4,500
- Minimum front setback 5'; maximum 15'; it is recommend building placement adjust to coordinate with adjacent conditions; expectations for transitional spaces included in the buildings increase as setbacks decrease; front of building parallel to and facing the corridor
- Minimum side and rear setbacks as zoned
- Use of on street parking or parking located on the first floor recommended
- On site parking lots are recommended located on the side or rear of the building
- It is recommended stormwater management consider the urban conditions by employing green roofs; installing collection/recycling stormwater systems; using stormwater planters; include plantings designed to serve multiple purposes; etc
- Parking located along sidewalk edge should provide a 3 1/2' evergreen hedge between the sidewalk and parking lot' planting bed should be a minimum of 4' wide.

Section/Plan B

- Recommended range of total square footage for new buildings: from 5,000 to 50,000; should be scaled to near-by existing buildings
- Maintain and / or establish a 50 foot wide (exclusive of the public right-of-way) forested edge and or hedgerow along the full length of Commerce Road frontage, protecting the existing character of a rural parkway, creating a buffer from future development, and establishing a matrix for future pedestrian and bike trail network throughout the City
- Off-street parking areas may include two layers of parking and one travel lane between the corridor and new development, with remaining parking located to the side or back of the building. Front of building parallel to and facing the corridor with adjustments appropriate in response to existing ridge lines or other landscape features



- Minimum front, side, and back setbacks as per underlying zoning with adjustments to coordinate with adjacent conditions; with setbacks of 25 feet or greater, expectations for transitional spaces included in

the buildings increase

- It is recommended stormwater management consider employing green roofs; installing collection/re-cycling stormwater systems; using stormwater planters; include plantings designed to serve multiple purposes; etc
- Parking located along sidewalk edge should provide a 3 1/2' evergreen hedge between the sidewalk and parking lot' planting bed should be a minimum of 4' wide.

Section/Plan C

- Recommended range of total square footage for new buildings: from 2,000 to 50,000; should be scaled to near-by existing buildings
- Off-street parking areas may include two layers of parking and one travel lane between the corridor and new development, with remaining parking located to the side or back of the building. Front of building parallel to and facing the corridor
- Minimum front, side, and back setbacks as per underlying zoning with adjustments to coordinate with adjacent conditions; with setbacks of 25 feet or greater, expectations for transitional spaces included in the buildings increase



houses and neighborhood corner gas station share coordinated setbacks

- It is recommended stormwater management consider employing green roofs; installing collection/re
- cycling stormwater systems; using stormwater planters; include plantings designed to serve multiple purposes
- Parking located along sidewalk edge should provide a 3 1/2' evergreen hedge between the sidewalk and parking lot' planting bed should be a minimum of 4' wide.


Floodway

- Multi-storied buildings with parking located on the first floor are recommended for new construction in the floodway / flood plain.

Stream Buffer Plantings

- Plant communities, as part of the overall creek system, serve to slow the velocity of stormwater run off, prevent erosion, and filter non-point pollution. Site design focused on preserving and managing indigenous riparian plant communities through thoughtful site design and maintenance is encouraged; the re-establishment of riparian plant communities as part of site design is recommended.

Rehabilitation District: for the purpose of tax abatement for new construction



City of Staunton, Virginia
Amy Ransom Arnold, ASLA



Planning and Inspections Department
2009
(as amended, 2.10.11)